



WR Methodological Module

Estimation of baseline carbon stock changes and greenhouse gas emissions from Wetland Restoration with hydrologic management including projected wetland loss in the baseline scenario (BL-WR-HM-WL)

I. SCOPE, APPLICABILITY AND PARAMETERS

Scope

This module allows for estimating carbon stock changes and GHG emissions related to Wetland Restoration (WR) in the baseline case when the baseline includes projected wetland loss and the project activity will include hydrologic management. Examples of eligible hydrologic management project activities include:

- a.* Diversion of river water (e.g., Mississippi River or other) into wetlands;
- b.* Introduction of nonpoint source runoff (e.g., agricultural, stormwater) into wetlands;
- c.* Discharge of treated municipal effluent into wetlands (e.g., wetland assimilation).
- d.* Outfall management to maximize sheetflow and minimize impounded or stagnant conditions.

Implementing a wetland restoration activity not only enhances vegetative productivity and carbon sequestration, but also may prevent further wetland loss. This module accounts for baseline sequestration that would decrease over time as wetlands degrade and convert into open water. This module conservatively does not account for the fate and transport of carbon during wetland loss that may result in emissions due to oxidation of soil organic carbon.

Applicability

The module is applicable for estimating baseline carbon stock changes and GHG emissions related to wetland restoration (WR) through hydrologic management, or through the combination of hydrologic management with assisted natural regeneration, seeding, or tree planting. The following conditions must be met to apply this module.

- Project activities meet the applicability conditions in the **WR-MF** listed under All Activity Types, and Wetland Restoration with Hydrologic Management.
- Project activities that increase emissions beyond the baseline scenario must be accounted for.
- All Hydrologic Management activities shall be demonstrated to be conducted in compliance with applicable environmental regulations and required permits.

Parameters

This module provides procedures to determine the following parameters:

| Parameter | SI Unit | Description |
|-----------------------------|----------------------|--|
| $\Delta C_{bsl,WR-HM-WL}$ | t CO ₂ -e | Cumulative total carbon stock changes and greenhouse gas emissions for the baseline scenario including projected wetland loss when the project activity will include hydrologic management |
| $\Delta C_{SOC_BSL_loss}$ | t CO ₂ -e | Cumulative total carbon stock changes of soils for the baseline scenario including wetland loss that would occur in the absence of project implementation |

II. PROCEDURE

- Step 1: Identification of baseline scenario
- Step 2: Project boundary
- Step 3: Baseline stratification
- Step 4: Baseline net GHG removals for fixed baselines
- Step 5: Monitoring requirements for baseline renewal

Part 1. Identification of the baseline scenario

Baseline determination is defined from Paragraph 22 of the CDM A/R Modalities and Procedures as “existing or historical, as applicable, changes in carbon stocks in the carbon pools within the project boundary” where the land would remain degraded in the absence of the project activity. Project Proponent must demonstrate that the land would remain degraded in the absence of the project activity by applying the tool **T-DEG**. This may be accomplished by using multiple sources of data, such as from peer-reviewed literature, archives, maps or satellite images of the land use/cover prior to project activity, field surveys, governmental reports, expert judgment¹ and interviews with land owners or professionals affiliated with wetland management of the area. Project Proponent must demonstrate that the candidate baseline scenario does not alter historical wetland patterns by analyzing the historical and existing wetland over the most recent 10-year period prior to the project start date, or longer if necessary, to demonstrate baseline historical wetland patterns.

Part 2. Project boundary

The WR baseline scenario is the carbon stock present immediately prior to site preparation, or the most likely carbon stock in the absence of project implementation as determined in step 1. The “project boundary” geographically delineates the WR project activity under the control of

¹ Justification should be supplied for all values derived from expert judgment.

the Project Proponent (PP) as defined in the **WR-MF**. It shall be demonstrated that each discrete parcel of land to be included in the boundary is eligible for an WR ACR project activity.

The pools that will be included or excluded from accounting are provided in **WR-MF**. **WR-MF** shall be followed in determining the GHG assessment boundary, along with the guidance in the *ACR Forest Carbon Project Standard*, Chapter 2.

Hydrologic management has the potential to increase GHG emissions therefore baseline and project emissions must be accounted for. Emissions may be estimated based on site/project specific data, an acceptable proxy, reference sample plots or field monitoring of similar sites, peer-reviewed literature, approved local or national parameters, or the most recent default emission factors provided by IPCC (e.g. IPCC 1997, 2003, 2006). Project Proponent using extrapolated values must make conservative estimates to determine the baseline and proposed project activity GHG emissions. Sources deemed significant and selected for accounting in the baseline scenario shall also be accounted for in the project scenario.

Exclusion of carbon pools and emission sources is allowed subject to considerations of conservativeness and significance testing. This may be accomplished by using multiple sources of data, such as from peer-reviewed literature, field surveys, governmental reports, and expert judgment². Pools or sources may always be excluded if conservative, i.e. exclusion will tend to underestimate net GHG emission reductions/removal enhancements. Pools or sources can be neglected (i.e., counted as zero) if application of the tool **T-SIG** indicates that the source is insignificant, provided that all sources, sinks and pools determined to be insignificant and excluded from accounting represent less than 3% of the *ex ante* calculation of emission reductions/removal enhancements (per *ACR Forest Carbon Project Standard*). If monitoring of baseline and project emissions determines that an emission source(s) initially included in the GHG assessment boundary is insignificant using the tool **T-SIG**, monitoring may cease.

Part 3. Baseline stratification

When estimating baseline carbon stocks, several strata can be assessed, including but not limited to:

- a. Management regime
- b. Vegetation type and species
- c. Age class
- d. Trend in land loss conversion
- e. Water quality (e.g. salinity, nutrient inputs, distance from source, etc.)
- f. Hydrology
- g. Elevation and subsidence rates
- h. Site index and anticipated growth rates

² Justification should be supplied for all values derived from expert judgment.

If the project activity area is not homogeneous, stratification should be carried out to improve the accuracy and precision of carbon stock estimates. Different stratifications may be required for the baseline and project scenarios, especially if there will be a change in hydrology, in order to achieve optimal accuracy and precision of the estimates of net GHG removal by sinks. For estimation of baseline net GHG removals by sinks, or estimation of actual net GHG removals by sinks, strata should be defined based on parameters that affect GHG removals or emissions and/or that are key entry variables for the methods used to measure changes in biomass stocks.

- **For baseline net GHG removals by sinks.** It will usually be sufficient to stratify according to major vegetation types since baseline removals for degraded (or degrading) wetlands can be expected to be small in comparison to project removals;
- **For actual net GHG removals by sinks.** The stratification for *ex-ante* estimations shall be based on the project monitoring plan. The stratification for *ex-post* estimations shall be based on the actual implementation of the project monitoring plan. If natural or anthropogenic impacts (e.g., hurricanes) or other factors (e.g. altered hydrology) add variability to the growth pattern of the project area, then the *ex-post* stratification shall be revised accordingly.

Project Proponent may use remotely sensed data acquired close to the time of project commencement and/or the occurrence of natural or anthropogenic impacts for *ex-ante* and *ex-post* stratification.

Part 4. Baseline net removals for fixed baselines

The WR wetland baseline scenario is the carbon stock present immediately prior to site preparation or the most likely carbon stock in the absence of project implementation. Therefore, the baseline net GHG removals by sinks is the sum of the changes in carbon stocks in the selected carbon pools within the project boundary just prior to site preparation or what would have occurred in the absence of the project activity.

Under the applicability conditions of this methodology:

- Changes in the carbon stock of aboveground and belowground biomass of non-tree vegetation may be conservatively assumed to be zero for all strata in the baseline scenario;
- Changes in the carbon stock of dead wood and litter/surface debris carbon pools are conservatively omitted. Therefore, the sum of the changes in the carbon stocks of dead wood and litter carbon pools is zero for all strata in the baseline scenario;
- For wetland GHG emissions, the sum of emissions will either be set as zero or quantified based on the conclusions of Step 2. Project Proponent using extrapolated

values must use conservative estimates.

The baseline net GHG removals by sinks shall be estimated using the equations in this section. When applying these equations for the *ex-ante* calculation of baseline net GHG removals by sinks, Project Proponent shall provide estimates of the values of those parameters that are not available before the start of the crediting period and commencement of monitoring activities. Project Proponent should retain a conservative approach in making these estimates.

4.1 Baseline carbon stocks³

The net carbon stock changes in the baseline are equal to the baseline living tree biomass stock plus the soil organic carbon stock that includes projected wetland loss minus the baseline greenhouse gas emissions. The baseline net GHG removals by sinks should be determined as:

$$\Delta C_{\text{bsl}, \text{WR-HM-WL}} = (\Delta C_{\text{TREE_BSL}} + \Delta C_{\text{SOC_BSL_loss}}) - \Delta \text{GHG}_{\text{E_BSL}} \quad (1)$$

where:

$\Delta C_{\text{bsl}, \text{WR-HM-WL}}$ Cumulative total of the carbon stock changes and greenhouse gas emissions for the baseline scenario up to time t ; t CO₂-e

$\Delta C_{\text{TREE_BSL}}$ Cumulative total of the carbon stock changes of living tree biomass for the baseline scenario up to time t ; t CO₂-e

$\Delta C_{\text{SOC_BSL_loss}}$ Cumulative total of the carbon stock changes of soils for the baseline scenario including wetland loss that would occur in the absence of project implementation up to time t ; t CO₂-e

$\Delta \text{GHG}_{\text{E_BSL}}$ Cumulative total of the change in carbon emissions for the baseline scenario t ; t CO₂-e

For calculation of carbon stock sequestered in living tree biomass see the module “Estimation of carbon stocks in tree biomass” (CP-TB). For calculation of carbon emissions see the module “Estimation of emission sources” (E-E).

4.2 Baseline carbon stock changes in soil pool including wetland loss ($\Delta C_{\text{SOC_BSL_loss}}$)

Project Proponent may conservatively quantify carbon stock changes in soil pool including projected wetland loss in the baseline scenario. For calculation of carbon stock sequestered in soils see the module “Estimation of carbon stocks in the soil organic carbon pool” (CP-S). The estimation of carbon stock changes in the soil in the baseline scenario ($\Delta C_{\text{SOC_BSL}}$) from CP-S will be modified to ($\Delta C_{\text{SOC_BSL_loss}}$) using the equations below. These equations provide for the calculations to be performed for each stratum. If there is more than one stratum in the

³ Stock estimates shall occur for the pools defined through the framework module WR-MF

baseline scenario, the outcome will be summed over all the strata to obtain the value for the whole project.

$$\Delta C_{SOC_BSL_loss} = (H_t/H_o) * \Delta C_{SOC_BSL} \quad (2)$$

where:

$\Delta C_{SOC_BSL_loss}$ Cumulative total of the carbon stock changes of soils for the baseline scenario including wetland loss that would occur in the absence of project implementation up to time t ; t CO₂-e

ΔC_{SOC_BSL} Cumulative total of the carbon stock changes of soils for the baseline scenario up to time t ; t CO₂-e (CP-S)

$$H_t = H_o - h * t \quad (3)$$

where:

H_t Project area at time t ; ha

H_o Project area at time $t=0$; ha

h Baseline land loss per year in the project boundary projected over the life of the project in the absence of project implementation; ha yr⁻¹

t time after project initiation; yr⁴

Rate of Wetland loss (h)

This module requires knowledge of the rate at which the project area wetlands would be lost to give an area per stratum (i) per year (t) through the project period (i.e., area of wetland loss per year). The baseline wetland loss in hectares per year in the project boundary must be determined before the start of the project activity. Project Proponent must make conservative estimates.

In the simplest scenario, the factors of wetland loss are already defined and the site has specific sources of data, such as from peer-reviewed literature, archives, maps or satellite images of the land use/cover prior to project activity, field surveys, and governmental reports to provide a justified rate of wetland loss.

If no verified rate exists, the rate will be established by examining proxy areas. The proxy area will be used to estimate an average proportion of wetlands that is lost each year, thus a

⁴ t cannot be longer than the H_o divided by h at which time the entire project area will have converted to open water.

sufficient number of parcels are needed to be representative of the wetland loss factors in the proxy area, and hence also in the project area. Examination of proxy areas may be through original data collection (field measurements and/or remote sensing analysis) or where appropriate use of directly applicable existing data generated from credible sources.

The following criteria for applicability of proxy areas to determine wetland loss rates must be met:

- a. **The main factor(s) of wetland loss** in the proxy at the start of the historical reference period must be the same as those expected to cause wetland loss in the project area during the project term. The historical reference period is defined as the historical period prior to the project start date that serves as the source of data for defining the baseline. Examples of factors include:
 - Flood control levees/ elimination of riverine inputs
 - Impoundment
 - Reduced sediment load
 - Salinity intrusion
 - Subsidence / Relative Sea Level Rise (RSLR)
 - Lack of freshwater
 - Lack of nutrient inputs
- b. **Policies, regulations, and programs** adopted at the national or regional level must influence the proxy area in the same way, or have an equivalent effect at the start of the historical reference period, taking into effect the current level of enforcement and program implementation (restoration programs).
- c. **Transportation networks and human infrastructure**, such as navigable rivers and canals, that increase the likelihood of wetland loss and that exist historically in the proxy area must be directly comparable to those that are expected to exist within the project area during the project term.
- d. **Wetland management** in the proxy area will be the same as in the project area under business as usual. The proxy area shall have the same proportions of wetland types as in the project area (+/- 20%)

When using proxy areas to determine baseline wetland loss the following equation may be used:

$$\Delta C_{SOC_BSL_loss} = h_{i,t} * \Delta C_{SOC_BSL} \quad (4)$$

where:

$\Delta C_{SOC_BSL_loss}$ Cumulative total of the carbon stock changes of soils in the baseline scenario including wetland loss that would occur in the absence of project implementation up to time t ; t CO₂-e

ΔC_{SOC_BSL} Cumulative total of the carbon stock changes of soils in the baseline scenario up to time t ; t CO₂-e (CP-S)

$h_{i,t}$ Projected annual proportion of wetland that will be lost in stratum i during year t ; %

If actual annual proportion of wetland that will be lost is known and documented, e.g. 25% per year for 4 years, then set $h_{i,t}$ to this proportion. Alternately if estimating the rate of wetland loss from a proxy area, set

$$h_{i,t} = (\sum_{pn=1}^{n*} (h\%_{pn} / Yrs_{pn})) / n \quad (5)$$

where:

$h_{i,t}$ Projected annual proportion of wetland that will be lost in stratum i during year t ; %

$h\%_{pn}$ Percent of wetland loss in land parcel⁵ pn etc of a proxy area as a result of wetland loss factors identified in this module; %

Yrs_{pn} Number of years over which wetland loss occurred in land parcel pn in proxy area; years

n Total number of land parcels examined

pn 1,2,3,... n * land parcels examined in proxy area

i 1,2,3,... M strata

Step 5. Monitoring requirements for baseline renewal

A crediting period for a project is a predetermined length of time for which the baseline scenario is applicable. This period of time is used for carbon quantification of offsets generated relative to its baseline.

Crediting periods can be renewed when Project Proponent⁶:

- Re-submit the GHG Project Plan in compliance with then-current GHG Program standards and criteria;
- Re-evaluate the project baseline;

⁵ Parcels are a unit of land area. A stratum may contain many parcels.

⁶ American Carbon Registry, 2010. American Carbon Registry Forest Carbon Project Standard, version 2.1. Winrock International, Little Rock, Arkansas. <http://www.americancarbonregistry.org/carbon-accounting/forest-carbon-project-standard-v2.0>. Last Accessed: June 6, 2010. 63 pages.

- Demonstrate additionality against then-current regulations and performance standard data.
- Use GHG program-approved baseline methods, emission factors, tools, and methodologies in effect at the time of crediting period renewal;
- Undergo verification by an approved verifier.

DATA AND PARAMETERS NOT MONITORED

| | |
|---|---|
| Data /parameter: | h |
| Data unit: | ha year^{-1} |
| Used in equations: | 3 |
| Description: | Baseline land loss per year in the project boundary projected over the life of the project in the absence of project implementation |
| Source of data: | Peer-reviewed literature, archives, maps or satellite images of the land use/cover prior to project activity, field surveys, and governmental reports. |
| Measurement procedures (if any): | N/A |
| Any comment: | |
| Data /parameter: | $h_{i,t}$ |
| Data unit: | $\% \text{ year}^{-1}$ |
| Used in equations: | 4, 5 |
| Description: | Projected annual proportion of wetland that will be lost in stratum i during year t |
| Source of data: | Analysis of remote sensing data and/or peer-reviewed literature, archives, maps or satellite images of the land use/cover prior to project activity, field surveys, governmental reports, expert judgment for a number of proxy areas |
| Measurement procedures (if any): | N/A |
| Any comment: | Shall be revisited at the time of baseline renewal |

PARAMETERS ORIGINATING IN OTHER MODULES

| | |
|--|--|
| Data /parameter: | $\Delta C_{\text{TREE_BSL}}$ |
| Data unit: | t CO ₂ -e |
| Used in equations: | 1 |
| Description: | Cumulative total of the carbon stock changes of living tree biomass in the baseline scenario |
| Module parameter originates in: | CP-TB |
| Any comment: | |

| | |
|--|---|
| Data /parameter: | ΔGHG_{E_BSL} |
| Data unit: | t CO ₂ -e |
| Used in equations: | 1 |
| Description: | Cumulative total of the change in carbon emissions of the baseline scenario |
| Module parameter originates in: | E-E |
| Any comment: | |

| | |
|--|---|
| Data /parameter: | $\Delta C_{\text{SOC_BSL}}$ |
| Data unit: | t CO ₂ -e |
| Used in equations: | 2, 4 |
| Description: | Cumulative total of the carbon stock changes of soils for the baseline scenario |
| Module parameter originates in: | CP-S |
| Any comment: | |